The Thermoclad Company ▸ ▸ ▸ ▸ ▸ ▸ ▸ Technical Data Sheet

DURATOP UVMT-1003C, Clear UV Cure Coating

Description: Zero (0) VOC, Clear decorative topcoat for various metal substrates.

Application: Roll Coat, Spray, etc.

Substrates: Aluminum, Steel, Galvanized & Other Metals

Film Build: 0.3 - 2 Mils

UV Care: 50-200 ft/min, H Bulb In and Out of Focus

Clean Up: Acetone, Acetates and etc.

Storage: Product should be stored inside away from heat & light.

FEATURES

Hardness, Durability, Excellent Adhesion, Mar. and Outdoor Weatherability

Physical Properties:

Specific Gravity:	1.02 ± 0.05
Viscosity #3 Zahn:	25 ± 2
VOC:	0
Tape Adhesion:	5B
Gloss @ 60°:	95-100
Storage Shelf Life:	Good

SAFE HANDLING PROCEDURES

Avoid contact with skin and eyes. Latex rubber gloves, safety glasses and rubber footwear are advised when handling this material. In case of contact with skin, wash immediately with water, **DO NOT USE SOLVENTS.** In case of eye contact, rinse immediately with after for at least 15 minutes and seek medical attention.

The above properties are based upon tests and data believed to be reliable, since actual use by others is beyond our control, no guarantee, expressed or implied is made by The Thermoclad Company as to the effects of such use or results to be obtained.

Corporate Office ▾ 361 West 11th Street ▾ Erie, PA 16501-1703 ▾ PH 814.456.1243 ▾ FX 814.459.2853
E-mail info@thermoclad.com / www.thermoclad.com
The above properties of DURAVIN or DURATOP products are based upon tests and data believed to be reliable, since actual use by others is beyond our control, no guarantee, expressed or implied, is made by The Thermoclad Company as to the effects of such use or results to be obtained.